



HYDAC INTERNATIONAL

KINESYS Area / 節能動力單元系統領域

HEZ-electric cylinders version U

U型電動缸-行動裝置設備應用

整組插拔組裝模式 (Plug & Play)

KINESYS



KINESYS

DESCRIPTION

The KineSys HEZ – electric cylinders version U are suitable for the use in mobile machinery and equipment. The compact closed housing protects from environmental influences. The selectable line voltage of the motors provides a wide range of applications in vehicle and industrial sector. A displacement encoder can be integrated.

FEATURES

- Positioning force up to 6,8 kN dynamic, 18 kN static
- Speed 11 – 54 mm/s
- Stroke 50 – 600 mm
- Installation of proximity switches possible
- Protection class up to IP 65
- Line voltage 12, 24, 36 VDC and 230, 400 VAC



- .小巧免維護
- .可油缸整合極限開關或是encoder
- .動態出力可達680Kg、靜態出力可達1800Kg.
- .採用DC 12, 24, 36伏特，或是AC 交.流230, 400伏特。
- .行程50-600 mm.
- .速度11-54 mm/s.

PRODUCT ADVANTAGES

- Compact design
- Service-free
- Integration of limit switches on the cylinder
- Integration of displacement encoder is possible
- Plug-and-Play ready